

For the SWIVELLING version add the suffix "/SO" at the P/N, except for the 560 series.
For example:
300/35/SO

FIXED PAINTED STEEL

FIXED S. STEEL AISI 304

Supplied with:

- hose in black synthetic rubber with galvanized steel coupling
- AISI 304 stainless steel swivel joint
- "Teflon" seals
- central shaft in galvanized steel or stainless steel AISI 304
- inlet hose 0,6 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	P/N	Hose supplied	Connection		
				Inlet	Outlet	
400 bar	S. 300	300/35	302/35	without hose	F 3/8"G	F 3/8"G
		300/36	302/36	12m 5/16" (945/12)	F 3/8"G	F 3/8"G
	S. 350	350/35	352/35	without hose	F 3/8"G	F 3/8"G
		350/36	352/36	12m 5/16" (945/12)	F 3/8"G	F 3/8"G
		350/37	352/37	17m 5/16" (945/17)	F 3/8"G	F 3/8"G
	S. 430	430/35	434/35	without hose	F 3/8"G	F 1/2"G
		430/38	432/38	10m 3/8" (907/10)	F 3/8"G	F 3/8"G
		430/39	432/39	15m 3/8" (907/15)	F 3/8"G	F 3/8"G
	S. 4430 ABS	-	4434/35	without hose	F 3/8"G	F 1/2"G
		-	4432/38	10m 3/8" (907/10)	F 3/8"G	F 3/8"G
		-	4432/39	15m 3/8" (907/15)	F 3/8"G	F 3/8"G
	S. 530	530/35	534/35	without hose	F 3/8"G	F 1/2"G
		530/36	532/36	20m 3/8" (907/20)	F 3/8"G	F 3/8"G
		530/37	532/37	25m 3/8" (907/25)	F 3/8"G	F 3/8"G
	S. 540	540/35	544/35	without hose	F 3/8"G	F 1/2"G
		540/36	542/36	30m 3/8" (907/30)	F 3/8"G	F 3/8"G
	S. 560	560/35	564/35	without hose	F 3/8"G	F 1/2"G
		560/36	562/36	40m 3/8" (907/40)	F 3/8"G	F 3/8"G
560/37		562/37	50m 3/8" (907/50)	F 3/8"G	F 3/8"G	
700 bar	S. 430	430/550	434/550	without hose	F 3/8"G	F 1/2"G
	S. 530	530/550	534/550	without hose	F 3/8"G	F 1/2"G
	S. 540	540/550	544/550	without hose	F 3/8"G	F 1/2"G

Rubber handles, mounted on hose terminal part, are available for all the above series. For more information look at page 50.



Atex 94/9

- ▶ II 3GD c X (only for series 300-350-4430 ABS)
- ▶ IIB 2GD c T4 T135°C X

USES

