



88 Series 8840 . 8860 . 8880



Acqua calda
Hot Water



Per uso professionale
For professional usage



Accessori professionali
Professional accessories

TSS[®]
Total Stop
SYSTEM

Caratteristiche Generali - General Features:



- Pompa a 3 pistoni in ceramica con sistema biella-manovella
- Testa pompa in ottone
- Valvola di by-pass automatica con azzeramento della pressione nella testa della pompa
- Motore elettrico trifase con protezione termica
- Sistema di arresto totale dell'idropulitrice a distanza
- Pressostato di sicurezza per spegnimento della caldaia in caso di mancanza acqua
- Caldaia verticale in acciaio inox, con sistema di raffreddamento bruciatore a chiocciola azionata da motore elettrico indipendente, doppia serpentina e fondo in cemento refrattario
- Scheda micropertite con segnalatore acustico
- Scheda di ritardo per spegnimento caldaia
- Regolazione pressione
- Serbatoio gasolio 24 l, con tappo di scarico
- Termostato
- Aspirazione detergente incorporata
- Serbatoio detergente 8 l incorporato
- Filtro acqua e filtro aspirazione gasolio
- Lunghezza cavo elettrico 10 m
- Triplex pump with ceramic pistons and connecting rod system
- Brass pump head
- Automatic by-pass valve with pump head pressure discharge
- Heavy-duty three-phase motor with thermal protector
- Remote control for total shut-down of high pressure cleaner
- With safety pressure switch to shut down the boiler in case of lack of water
- Stainless steel vertical boiler with coil burner cooling function driven by independent motor, double coil and refractory cement bottom
- Minor leak detector PCB with buzzer
- Heating boiler shut-down delay circuit
- Pressure adjustment built-in
- Fuel tank with drain plug (24 l)
- Thermostat
- Built-in detergent suction
- Built-in detergent tank capacity 8 l
- Water filter and fuel inlet filter
- Electric cable length 10 m

Fornito con - Equipped with:

MV951
Pistola 3/8"(F) - M22x1,5 con prolunga
Trigger gun with extension
(41089)



Tubo AP 10 m armato
10 m reinforced HP hose
TDN8-Max 210° C (3160170)



Lancia
Lance
(50690)



Ugello 1/4 MEG
Wash nozzle
8840 (3157) - (1508)
8860 (3084) - (1506)
8880 (3082) - (1504)



Vaschetta acqua
con galleggiante di serie
Water tank with float switch
as standard



(HXW)

Dati Tecnici / Technical Data

MOD	COD	MAX		l/h		⚡			🌡️			⚖️		
		bar	psi	l/h	gph	kW	rpm	Hz	V	HP	°C	°C Max	Δt	kg
8840	22913	150	2200	1260	333	7,4	1450	3~50	400	7,5	30	150	55	135
8860	22914	200	2900	1260	333	9,3	1450	3~50	400	10	30	150	55	135
8880	22915	250	3600	900	238	9,3	1450	3~50	400	10	30	150	65	135

Temperatura massima acqua / Max inlet water temperature 60°C 140°F - IPX5-S1