

Fuel trolley [PG 4]

Fuel trolley 53l

- UN approved for the transport of fuel
- HD-PE container 53 l with wheel and handle for maneuverability
- delivery nozzle pump, 7.5 l/min, with 3 m delivery hose and locking catch for the trigger guard
- baffle
- filling tubes with integrated ventilation
- 2 shut-off valves for problem-free dismantling of the delivery hose
- integrated recesses for securing the trolley with ratchet lashing strap during transport



Fuel trolley 95l

- suitable for use under ADR 1.1.3.1 c) for single site refuelling by a person in the course of their main business
- container constructed from high density electrically conductive polyethylene to eliminate static
- patented flame suppressive filling
- integral grip and carry handles
- filling cap with integral breather valve
- delivery hose with stop valve
- handpump 25l/min with 3 m conductive delivery hose and nozzle
- 300 mm diameter pneumatic tyres
- internal baffle
- integral nozzle holder
- moulded recesses for strapping during transport



NEW

Fuel trolley

Designation/Capacity	Dimensions in cm (l x w x h)	Weight approx. kg	Order no.
Fuel trolley 53l	87 x 42 x 33	9	10047
Fuel trolley 95l *	100 x 59 x 43	20	10162

* Available december 2012

Technical specifications and prices subject to change.