



HIGH PRESSURE HYDRAULIC EQUIPMENT PRODUCT OVERVIEW




**NEW
MODELS**




34-039 ENG 10-2019 © Larzep - Subject to change without notice.

Type	W - X
Capacity	0,28 - 6,5 litres
Max. pressure	700 bar




SINGLE ACTING W

W20307 / W10607 / W20807 / W11407 / W21807




W22607 / W24507




DOUBLE ACTING X

X22607 / X24307



SINGLE / DOUBLE ACTING W - X

W26507 / X26507



- ✔ **W** series pumps are for use with **Single Acting** cylinders.
- ✔ **X** series pumps are fitted with 4-way 3 position valve for use with **Double Acting** cylinders.
- ✔ The pump range includes single and two speed models.
- ✔ Two speed models provide rapid cylinder advance until contact is made with the load.
- ✔ Hydraulic port on all models is 3/8"-NPTF female.
- ✔ W and X series pumps are fitted with internal safety valves to prevent overpressure.
- ✔ W24507 has a rectangular tank.
- ✔ WP21007 and XP21007 models are foot pedal operated.
- ✔ All pumps are fitted with handle or handle clips for ease of carrying.



WP21007 pump, foot pedal operated.



W26507, X26507 pumps.

SINGLE ACTING

Model	Speeds	Usable oil	Handle effort	Oil displacement / stroke (cm ³)		Pressure rating (bar)		A	B	C	D	E	G	R	S	T	Weight	Model
LARZEP	No.	cm ³	kg	1 st Stage	2 nd Stage	1 st Stage	2 nd Stage	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	LARZEP
W20307	2	280	40	7	1,0	20	700	331	138	124	44	380	-	7	38	66	5,5	W20307
W10607	1	640	43	-	3,2	-	700	557	137	144	55	608	-	-	-	90	7,3	W10607
W20807	2	640	45	13	2,8	17	700	563	137	144	55	608	-	-	-	90	8,2	W20807
WP21007	2	1.000	43	12	2,0	50	700	550	176	445*	52	540	-	9,0	185,0	176	9,0	WP21007
W11407	1	1.400	43	-	3,2	-	700	526	137	174	55	608	-	-	-	106	10,9	W11407
W21807	2	1.800	49	13	2,8	21	700	548	147	174	23	558	-	10,5	82,0	140	11,3	W21807
W22607	2	2.600	41	46	4,0	28	700	656	140	186	41	680	616	10,5	80,5	10	12,7	W22607
W24507	2	4.450	43	46	4,0	28	700	574	146	189	41	643	528	10,5	80,5	10	18,1	W24507
W26507	2	6.500	37	126	4,9	28	700	635	312	233	191	640	-	-	-	-	20,0	W26507

* with the pedal completely open

DOUBLE ACTING

Model	Speeds	Usable oil	Handle effort	Oil displacement / stroke (cm ³)		Pressure rating (bar)		A	B	C	D	E	F	H	R	S	Weight	Model
LARZEP	No.	cm ³	kg	1 st Stage	2 nd Stage	1 st Stage	2 nd Stage	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	LARZEP
XP21007	2	1.000	43	12,0	2,0	50	700	550	176	445*	52	540	-	-	9,0	185	9,0	XP21007
X22607	2	2.600	41	46,0	4,0	27	700	654	140	186	54	680	-	125	9,5	80,5	14,3	X22607
X24307	2	4.200	49	16,5	2,8	20	700	570	108	210	75	560	40	50	8,5	86	22,8	X24307
X26507	2	6.500	37	126,0	4,9	28	700	635	312	233	193	644	70	-	-	-	20,8	X26507