

DISPENSERS

SUZZARABLU PORTABLE KIT



EN. Portable Urea transfer unit with diaphragm pump complete with 12/230 V electric motor without dynamic seals. Thanks to this solution, a reliable industrial pump with self-priming features can be obtained.

Terminal box with switch and fuses to protect against overloads. 12/230V electric pump. 2-metre cables with battery-connection clamps. 6-metre hose for Urea - diameter 3/4". Manual plastic nozzle. Suction kit with EPDM 1.5 m hose and foot valve.

ES. Grupo portátil para el trasiego de Urea con bomba de membrana dotada de motor eléctrico 12/230V sin estanqueidades dinámicas. Esta solución permite obtener una bomba industrial fiable con capacidades autocebantes.

Caja de conexiones con interruptor y fusible para protección de sobrecargas. Electrobomba 12/230 V. Cables de 2 metros con pinzas de conexión a la batería. Tubo de 4 metros para Urea de 3/4" de diámetro. Pistola manual de plástico. Kit de succión con tubo de EPDM de 1,5 m y válvula de pie.

PT. Grupo portátil para transferência de Uréia com bomba de membrana dotada de motor elétrico 12/230V sem guarnições dinâmicas. Esta solução consente obter uma bomba industrial confiável com capacidade de auto disparo.

Caixa com painel de terminais com interruptor e fusível para a proteção de sobrecargas. Eletrobomba 12/230V. Cabos de 2 metros com pinças de ligação, com bateria. Tubo de 6 metros para Uréia, diâmetro 3/4". Pistola manual em plástico. Kit de aspiração com tubo EPDM 1,5 M e válvula de fundo.

PERFORMANCE

- Duty cycle 20 min

- Ciclo de trabajo de 20 min

- Ciclo de trabalho 20 min



PRODUCTS' RANGE WEIGHT AND PACKAGING

Code	Weight		Packaging		
	kg	lbs	mm	inch	pcs/box
F00201AA0	8	17,6	357x357x275	14,1x14,1x10,8	1
F00201C70	10	22	357x357x275	14,1x14,1x10,8	1

Flow-rate

up to
35 l/min
(up to 9,2 gpm)

PIUSI[®]

DISPENSERS

PUMPS

METERS

NOZZLE METERS

NOZZLE

SPECIAL EQUIPMENTS



FLUID MONITORING

ACCESSORIES

FILTERING



SUZZARABLU
PORTABLE KIT



FEATURES

ON REQUEST



PRODUCTS' RANGE TECHNICAL DATA

Code	Description	Fluids type	Flow-rate		Voltage			Nozzle type	Hose		On/Off switch
			l/min	gpm	AC V/Hz	DC Volt	Power Watt		Amp. max.	length	
F00201AA0	SuzzaraBlue KIT 12 V	U	35	9,2	12	260	22	Manual	6 m	3/4"	YES
F00201C70	SuzzaraBlue KIT 230 V	U	32	8,5	230/50	400	1,95	Manual	6 m	3/4"	YES