

Series Standard in PAINTED STEEL

Air - water

20 bar

swivel
seals
hose

Brass
Viton
Polyurethane



S. 430



S. 350



S. 300



S. 270




THE HOSE REELS ARE EQUIPPED WITH A UNIVERSAL HOSE STOP; THOSE WITH HOSE ARE PROVIDED WITH A 1,5 m INLET CONNECTION HOSE.


- The template supplied, facilitates drilling of the holes and therefore hose reel fixing.




- The quick coupling support (see page 82) that facilitates installation in battery is available on request.



- The quick coupling adjustable support (see page 82) that enables 40° rotation to the right or left of the hose reel is available on request.



- The adjustable arms can be easily repositioned according to needs (see page 77).



	Article	Capacity l/min Air-Water	Delivery hose	∅ Hose	Inlet connection	Outlet connection
Series 270	268/10	800 - 35	without hose	/	M 3/8"G	F 3/8"G
	268/12	690 - 30	13m (921/13)	10x14,5	M 3/8"G	M 3/8"G
	268/13	320 - 18	15m (911/15)	8x12	M 3/8"G	M 1/4"G
	268/14	280 - 10	10m (901/10)	6x10	M 3/8"G	M 1/4"G
	268/15	250 - 8	15m (901/15)	6x10	M 3/8"G	M 1/4"G

N° 1 packing m³ 0,037 from kg 7 to 12

Series 300	298/10	800 - 35	without hose	/	M 3/8"G	F 3/8"G
	298/12	670 - 28	15m (921/15)	10x14,5	M 3/8"G	M 3/8"G
	298/13	300 - 15	18m (911/18)	8x12	M 3/8"G	M 1/4"G
	298/14	800 - 33	8m (961/8)	13x19	M 1/2"G	M 1/2"G
	298/15	780 - 31	12m (961/12)	13x19	M 1/2"G	M 1/2"G

N° 1 packing m³ 0,045 from kg 8 to 13

Series 350	348/10	800 - 35	without hose	/	M 3/8"G	F 3/8"G
	348/12	650 - 25	20m (921/20)	10x14,5	M 3/8"G	M 3/8"G
	348/13	280 - 13	20m (911/20)	8x12	M 3/8"G	M 1/4"G
	348/14	780 - 32	10m (961/10)	13x19	M 1/2"G	M 1/2"G
	348/15	760 - 30	15m (961/14)	13x19	M 1/2"G	M 1/2"G

N° 1 packing m³ 0,068 from kg 10 to 17

Series 430	430/10	800 - 50	without hose	/	F 1/2"G	F 1/2"G
	428/11	760 - 45	10m (961/11)	13x19	F 1/2"G	M 1/2"G
	428/12	740 - 42	15m (961/15)	13x19	F 1/2"G	M 1/2"G

N° 1 packing m³ 0,086 from kg 14 to 21

OVERALL DIMENSIONS

Series	A	B	C	D	E	F	G	H
270	186	140	196	226	110	310	300	320
300	186	140	196	226	110	355	350	365
350	186	140	196	226	110	400	390	410
430	186	140	196	226	115	450	420	460

