

THE HOSE REELS ARE EQUIPPED WITH A UNIVERSAL HOSE STOP; THOSE WITH HOSE ARE PROVIDED WITH A 0,6 m INLET CONNECTION HOSE. Relative Delivery hose Inlet Outlet Article ø Hose capacity onnecti connectio 300/30 30 l/min without hose F 3/8"G F 3/8"G Series The template 300/31 25 l/min 12m (943/12) 5/16" F 3/8"G F 3/8"G supplied, facilitates drilling of the holes 300 👔 N° 1 packing m³ 0,045 🛱 from kg 8 to 13 and therefore hose 350/30 30 l/min F 3/8"G F 3/8"G without hose reel fixing. 350/31 25 |/min 12m (943/12) F 3/8"G F 3/8"G Series 5/16' 350/32 24 l/min 17m (943/17) F 3/8"G F 3/8"G 5/16" 350 🎁 N° 1 packing 🛱 from kg 10 to 17 m³ 0,068 The quick coupling support (see page 82) F 3/8"G 430/30 30 l/min F 1/2"G without hose that facilitates installation 430/31 27 l/min 12m (955/12) F 3/8"G F 3/8"G 3/8" Series in battery is available on 430/32 18m (955/18) F 3/8"G 25 l/min 3/8" F 3/8"G request. 430 N° 1 packing m³ 0,086 🛱 from kg 14 to 24 530/30 30 l/min without hose F 3/8"G F 1/2"G The quick coupling 530/31 24 l/min 25m (955/25) F 3/8"G Series 3/8" F 3/8"G adjustable support 20m (955/20) (see page 82) that enables 40° rotation to the right or left of the 530/32 25 l/min 3/8" F 3/8"G F 3/8"G 530 😭 N° 1 packing m³ 0,120 🛱 from kg 19 to 42 hose reel is available 540/30 30 l/min without hose F 3/8"G F 1/2"G **Series** 540/31 22 l/min 30m (955/30) F 3/8"G F 3/8"G 3/8" on request. 540 😭 N° 1 packing 🛛 m³ 0,175 骨 from kg 24 to 50 560/30 The adjustable arms 30 l/min without hose F 3/8"G F 1/2"G can be easily repositioned 40m (955/40) F 3/8"G 560/31 20 I/min 3/8" F 3/8"G **Series** F 3/8"G 560/32 18 l/min 50m (955/50) F 3/8"G 3/8" 560

N° 1 packing


m³ 0,310


🛱 from kg 30 to 80

according to needs (see page 77).

OVERALL DIMENSIONS Series A В С D E F. G **300** 186 140 196 226 110 355 350 365 186 140 196 226 110 400 390

н





22