Series Industri Water - Hot w 200 bar		ESS STEE St.steel AlS Viton Black synth rubber	SI 304	ØE	<u>CODORA</u>
5. 560	5. 540	s. 530	5. 430	s. 350	s. 300

THE HOSE REELS ARE EQUIPPED WITH A UNIVER HOSE STOP; THOSE WITH HOSE ARE PROVIDED V A 0,6 m INLET CONNECTION HOSE.

The template supplied, facilitates drilling of the holes and therefore hose reel fixing.


 The quick coupling support (see page 82) that facilitates installation in battery is available on request.

 The quick coupling adjustable support (see page 82) that enables 40° rotation to the right or left of the hose reel is available on request.

The adjustable arms can be easily repositioned according to needs (see page 77).

**OVERALL DIMENSIONS** 

Series	Α	В	С	D	E	F	G	н
300	186	140	196	226	110	355	350	365
350	186	140	196	226	110	400	390	410
430	186	140	196	226	115	450	420	460
530	203	153	220	258	115	550	510	560
540	300	218	228	268	190	550	510	573
560	488	399	238	272	368	522	510	578



AL TH		Article	Relative capacity	Delivery hose	ø Hose	Inlet connection	Outlet connection	
_	Series	302/30 302/31	30 l/min 25 l/min	without hose 12m (943/12)	/ 5/16"	F 3/8"G F 3/8"G	F 3/8"G F 3/8"G	
	300							
Series 350		352/30	30 l/min	without hose	/	F 3/8"G	F 3/8"G	
	352/31 352/32	25 l/min 24 l/min	12m (943/12) 17m (943/17)	5/16" 5/16"	F 3/8"G F 3/8"G	F 3/8"G F 3/8"G		
	050		Î	🛱 from kg 10 to 17				
, <u> </u>	Series	434/30 432/31 432/32	30 l/min 27 l/min 25 l/min	without hose 12m (955/12) 18m (955/18)	/ 3/8" 3/8"	F 3/8"G F 3/8"G F 3/8"G	F 1/2"G F 3/8"G F 3/8"G	
<u> </u>	430		Î	N° 1 packing m³ 0,086	🛱 from kg 14	to 24		
	Series 530	534/30 532/31 532/32	30 l/min 24 l/min 25 l/min	without hose 25m (955/25) 20m (955/20) N° 1 packing m <sup>3</sup> 0,120	/ 3/8" 3/8"	F 3/8"G F 3/8"G F 3/8"G	F 1/2"G F 3/8"G F 3/8"G	
	Series	544/30 542/31	30 l/min 22 l/min	without hose 30m (955/30)	/ 3/8"	F 3/8"G F 3/8"G	F 1/2"G F 3/8"G	
	540		Î	N° 1 packing m <sup>3</sup> 0,175	🛱 from kg 24	to 50		
5	Series 560	564/30 562/31 562/32	30 l/min 20 l/min 18 l/min	without hose 40m (955/40) 50m (955/50)	/ 3/8" 3/8"	F 3/8"G F 3/8"G F 3/8"G	F 1/2"G F 3/8"G F 3/8"G	
	500			N° 1 packing m³ 0,310	from kg 30			

