



Push button - Spring

Coding: 224.1.8.1

Operational characteristics	
Fluid	Filtered air. No lubrication needed, if applied it shall be continuous
Max. working pressure (bar)	10
Temperature °C	-5 ... +70
Flow rate at 6 bar with $\Delta p=1$ (l/min)	1360
Orifice size (mm)	8
Working ports size	G1/4"

TYPE
1 32 = 3 ways, 2 positions
52 = 5 ways, 2 positions




3/2 ways



Weight 395 g
Operating force 71,5 N

224.32.8.1




5/2 ways



Weight 480 g
Operating force 71,5 N

224.52.8.1





Push button 2 positions

Coding: 224.1.8

Operational characteristics	
Fluid	Filtered air. No lubrication needed, if applied it shall be continuous
Max. working pressure (bar)	10
Temperature °C	-5 ... +70
Flow rate at 6 bar with $\Delta p=1$ (l/min)	1360
Orifice size (mm)	8
Working ports size	G1/4"

TYPE
1 32 = 3 ways, 2 positions
52 = 5 ways, 2 positions




3/2 ways



Weight 385 g
Operating force 13 N

224.32.8




5/2 ways



Weight 470 g
Operating force 13 N

224.52.8





Lever lateral - Spring

Coding: 224.1.9.1/C

Operational characteristics	
Fluid	Filtered air. No lubrication needed, if applied it shall be continuous
Max. working pressure (bar)	10
Temperature °C	-5 ... +70
Flow rate at 6 bar with $\Delta p=1$ (l/min)	1360
Orifice size (mm)	8
Working ports size	G1/4"

TYPE
1 32 = 3 ways, 2 positions
52 = 5 ways, 2 positions
LEVER COLOR
1 = Red
2 = Black
3 = Green




3/2 ways



Weight 520 g

224.32.9.1/C



5/2 ways



Weight 605 g

224.52.9.1/C

