



## Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

 Creation Date:
 17-12-2018


 Datasheet No:
 DS791W

 Parker Part No:
 PR2840Q

 OEM:
 Mahle

 OEM Part No:
 Pi44108SMX25

| OZIII I di t Ito:  |       | 1 144 1000M/X20 |      |
|--------------------|-------|-----------------|------|
|                    |       |                 |      |
| Product Dimensions |       |                 |      |
| A (mm)             | 47.0  | (inch)          | 1.85 |
| B (mm)             | 25.5  | (inch)          | 1.00 |
| D (mm)             | 47.0  | (inch)          | 1.85 |
| E (mm)             | 171.0 | (inch)          | 6.73 |





## **Construction Materials**

Top Endcap: Mild steel tin plated

Bottom Endcap: Mild steel tin plated

Inner Support Cylinder: Mild steel tin plated

Filter Media: Multilayer fibreglass with coated mesh on both sides

## **Calculated Performance Criteria**

 Differential Pressure (Δp):
 0.40 bar @ 150 l/min

 Tested to ISO3968 @ 32 cSt
 5.80 psi @ 33.00 gpm

Efficiency: >Beta 200 @ 20 microns & greater

>Beta 1000 @ 22 microns & greater

**Minimum Collapse Pressure:** >20 bar **Tested to ISO2941** >290 psi

## Dirt Holding Capacity acc. to ISO16889

13.3 gram @ 7 bar terminal pressure drop13.3 gram @ 102 psi terminal pressure drop

