



Feuerschutzschlauch mit Klettverschluss - EN45545 / DIN5510-2

Fire protection hose with velcro closure - EN45545 / DIN5510-2

Tuyau de protection contre l'incendie avec velcro - EN45545 / DIN5510-2

Manguera de protección contra incendios con velcro - EN45545 / DIN5510-2

Wąż przeciwpożarowy z zapięciem na rzep - EN45545 / DIN5510-2

Protezione antifiamma per tubi con velcro - EN45545 / DIN5510-2

Beschreibung:	Silikonbeschichtetes Fiberglas mit Klettver- schluss
Betriebstemperatur:	max 260°C kurzfristig 1100°C
Norm:	EN45545 und DIN5510-2 UL 1441
Rollenware:	<= DN75 20m > DN75 10m (kein Anschnitt)
Desription:	Silicone coated fibreglas with loop closure
Temperature:	max 260°C short time 1100°C
Norm:	EN45545 and DIN5510-2 UL 1441
Coil:	<= DN75 20m > DN75 10m (no short lengths available)

Part-No.	 mm	 mm	 bar	 mm	 %	 g/m	Price/m
SSCF-15-W	15	19,2					
SSCF-20-W	20	25					
SSCF-25-W	25	30,2					
SSCF-30-W	30	35,8					
SSCF-35-W	35	41,2					
SSCF-40-W	40	46,8					
SSCF-45-W	45	52					
SSCF-50-W	50	57,4					
SSCF-55-W	55	62,8					
SSCF-60-W	60	68					
SSCF-65-W	65	73,2					
SSCF-70-W	70	78,6					
SSCF-75-W	75	83,8					
SSCF-80-W	80	89					
SSCF-90-W	90	100					
SSCF-95-W	95	105					
SSCF-100-W	100	112					



Silikon Vulkanisierband

Silicone vulcanising tape

Bande de vulcanisation en silicone

Cinta vulcanizadora de silicona

Silikonowa taśma wulkanizacyjna

Nastro vulcanizzante in silicone

Part-No.	Colour	Length	Thickness	Width	Price
VB01-10M	Red	10m	0,5mm	25mm	
VB02-10M	Black	10m	0,5mm	25mm	